

FRT610 Fingerprint Scanner

Small size fingerprint reader



The ARATEK FRT610 is compliant with international standards including ISO and ANSI, guarantee high quality output at all times.

Features

- International Standard ISO19794-2, ISO19794-4, ANSI 378, ANSI 381 and WSQ supported
- High Image Quality
 Capacitive fingerprint technology with superior image quality
- Strong Adaption Good adaption for dry, moist and rough fingerprints
- Correction and Authentication Support auto correction and 360 degree rotation authentication
- Cloud Platform
 - Seamlessly join in Aratek TrustLink $^{\rm TM}$ biometrics authentication platform
- **OS Support** Windows 2000, XP, Vista, Windows 7/ 8/ 10, Android and other embedded systems
- SDK

Comprehensive software development kit is available for development and integration

Applications

- PC/NetworkSecurity
- Hospitality
- Finance and Banking

- Telecommunication
- Healthcare
- Law Enforcement

FRT610 Fingerprint Scanner

Physical Parameter		
Dimension (W*L*H)	50*100*15 mm	
		Far
Performance Parameter		
Sensor Type	Capacitive	
Platen Size (W*L)	13.5*15.3 mm	
Sensing Area (W*L)	12.8*14.4 mm	
Image Size	256*288 pixels	
Image Resolution	508 dpi	
Gray level	8 bits, 256 level	
Communication Mode	USB 1.1/2.0	
Operation Environment		
Work Voltage	5.0 V	
Work Current	≤50 mA	
Operating Temperature	0°C~55°C	
Operating Humidity	20~90%R.H	
ESD	Contact: ± 8KV, Air: ± 15KV	ARNTEK
Supported OS		
Windows XP/ 7/ 8/ 10, Android, Linux		

Aratek Biometrics Co., Ltd.

© 10F, No. 131, Songjiang Road, Zhongshan District, Taipei City 10491, Taiwan Kg +886 2-2501-0001 🖂 sales@aratek.co 🛛 🌐 www.aratek.co

©Copyright 2023. Aratek Biometrics Co., Ltd. Aratek logo is a registered trademark of Aratek or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademark of their respective owners. All specifications are subject to change without notice. All rights reserved.